

Простой пример вызова функций плагина

Google Chrome/Chromium

Если вы открываете локальную страницу, убедитесь, что в настройках расширения Адаптер Рутокен Плагин включена опция **"Разрешить открывать локальные файлы по ссылкам"**

```
-----
| . ra.rutoken.ru |
|-----
...

```



```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="UTF-8">

    <script type="text/javascript" src="rutoken.js"></script>
    <script type="text/javascript" src="scripts.js"></script>

  <title>Rutoken Plugin Tutorial</title>
  </head>
  <body>
    <pre>
-----
| |
| | . <a href="http://ra.rutoken.ru"> ra.rutoken.ru</a>
| |
|-----
    </pre>
    <div id="pluginStatus"><pre> ...</pre></div>
    <textarea rows="10" cols="95" id="textToSign" placeholder=" " ></textarea><br/>
    <button id="signButton" onclick="sign()" style="display: block; background: none; border: 4px solid black; font-
family: monospace; width: 20em; height: 3em; text-align: center; cursor: pointer;"> </button>
  </body>
</html>

```

```
// GOOGLE CHROME
//
//
// - .
//
// :
// promise.then(onFulfilled, onRejected)
// onFulfilled - ,
// onRejected - ,
//
//
// " "
var plugin;

function checkVersion(lastVersion) {
  if (plugin.version.toString() < lastVersion)
    console.log("download last version: " + lastVersion);
  else
    console.log("you have last version");
}

function getLastRtPluginVersion(callback) {
  var xhr = new XMLHttpRequest();
  xhr.open('GET', 'https://download.rutoken.ru/Rutoken_Plugin/Current/version.txt', true);
  xhr.onreadystatechange = function() {
    if (xhr.readyState == 4 && xhr.status == 200) {
      var lastPluginVersion = this.response.split('Version: v.')[1].split('Release')[0].replace(/\s+/g, '');
    }
  }
}

```

```

callback(lastPluginVersion);
}
};
xhr.send();
}

window.onload = function() {
  rutoken.ready
  // ' ' Google Chrome
  .then(function() {
    if (window.chrome || typeof InstallTrigger !== 'undefined') {
      return rutoken.isExtensionInstalled();
    } else {
      return Promise.resolve(true);
    }
  })
  //
  .then(function(result) {
    if (result) {
      return rutoken.isPluginInstalled();
    } else {
      return Promise.reject(" ' ");
    }
  })
  //
  .then(function(result) {
    if (result) {
      return rutoken.loadPlugin();
    } else {
      return Promise.reject(" ");
    }
  })
  //
  .then(function(result) {
    if (!result) {
      return Promise.reject(" ");
    } else {
      plugin = result;
      return Promise.resolve();
    }
  })
  .then(function() {
    document.getElementById("pluginStatus").innerHTML = "<pre> </pre>";
    getLastRtPluginVersion(checkVersion);
  }, function(msg) {
    document.getElementById("pluginStatus").innerHTML = "<pre>" + msg + "</pre>";
  });
}

//
// https://dev.rutoken.ru/display/PUB/RutokenPluginDoc
// CLASS: ERRORCODES
function handleError(reason) {
  if (isNaN(reason.message)) {
    alert(reason);
  } else {
    var errorCodes = plugin.errorCodes;
    switch (parseInt(reason.message)) {
      case errorCodes.PIN_INCORRECT:
        alert(" PIN");
        break;
      default:
        alert(" ");
    }
  }
}

sign = function() {
  var rutokenHandle, certHandle;
  //
  var textToSign = document.getElementById("textToSign").value;
  if (textToSign.length == 0) {
    alert(" ");
    return;
  }
  //
  plugin.enumerateDevices()
  .then(function(devices) {
    if (devices.length > 0) {
      return Promise.resolve(devices[0]);
    } else {
      return Promise.reject(" ");
    }
  })
}

```

```

    })
    //
    .then(function(firstDevice) {
        rutokenHandle = firstDevice;
        return plugin.getDeviceInfo(rutokenHandle, plugin.TOKEN_INFO_IS_LOGGED_IN);
    })
    //      PIN-
    .then(function(isLoggedIn) {
        if (isLoggedIn) {
            return Promise.resolve();
        } else {
            return plugin.login(rutokenHandle, "12345678");
        }
    })
    //
    .then(function() {
        return plugin.enumerateCertificates(rutokenHandle, plugin.CERT_CATEGORY_USER);
    })
    //
    .then(function(certs) {
        if (certs.length > 0) {
            certHandle = certs[0];
            var options = {};
            return plugin.sign(rutokenHandle, certHandle, textToSign, plugin.DATA_FORMAT_PLAIN, options);
        } else {
            return Promise.reject("    ");
        }
    })
    //      CMS
    .then(function(cms) {
        alert(cms);
    })
    //
    .then(function() {
        plugin.logout(rutokenHandle);
    }, handleError);
}

var rutoken = (function (my) {
    var loadCallbacks = [];
    var pluginMimeType = "application/x-rutoken-pki";
    var extension = window["C3B7563B-BF85-45B7-88FC-7CFF1BD3C2DB"];

    function isFunction (obj) {
        return !(obj && obj.call && obj.apply);
    }

    function proxyMember (target, member) {
        if (isFunction(target[member])) {
            return function () {
                return target[member].apply(target, arguments);
            };
        } else {
            return target[member];
        }
    }

    function returnPromise (promise) {
        return function () {
            return promise;
        };
    }

    function initialize () {
        my.ready = Promise.resolve(true);
        my.isExtensionInstalled = returnPromise(Promise.resolve(false));
        my.isPluginInstalled = returnPromise(Promise.resolve(true));
        my.loadPlugin = loadPlugin;
        window.rutokenLoaded = onPluginLoaded;
    }

    function initializeExtension() {
        var readyPromise = extension.initialize().then(function () {
            return extension.isPluginInstalled();
        }).then(function (result) {
            my.isExtensionInstalled = returnPromise(Promise.resolve(true));
            my.isPluginInstalled = proxyMember(extension, "isPluginInstalled");
        });

        if (result) {
            pluginMimeType = "application/x-rutoken-plugin";
            my.loadPlugin = loadChromePlugin;
        }
    }

```

```

return true;
});

my.ready = readyPromise;
}

function initializeWithoutPlugin () {
  my.ready = Promise.resolve(true);
  my.isExtensionInstalled = returnPromise(Promise.resolve(false));
  my.isPluginInstalled = returnPromise(Promise.resolve(false));
}

function loadPlugin () {
  var obj = document.createElement("object");
  obj.style.setProperty("visibility", "hidden", "important");
  obj.style.setProperty("width", "0px", "important");
  obj.style.setProperty("height", "0px", "important");
  obj.style.setProperty("margin", "0px", "important");
  obj.style.setProperty("padding", "0px", "important");
  obj.style.setProperty("border-style", "none", "important");
  obj.style.setProperty("border-width", "0px", "important");
  obj.style.setProperty("max-width", "0px", "important");
  obj.style.setProperty("max-height", "0px", "important");

  // onload callback must be set before type attribute in IE earlier than 11.
  obj.innerHTML = "<param name='onload' value='rutokenLoaded'/>";
  // Just after setting type attribute before function returns promise
  // FireBreath uses onload callback to execute it with a small delay.
  // So it must be valid, but it will be called a little bit later.
  // In other browsers plugin will be initialized only after appending
  // an element to the document.
  obj.setAttribute("type", pluginMimeType);

  document.body.appendChild(obj);

  var promise = new Promise(function (resolve, reject) {
    loadCallbacks.push(resolve);
  });

  return promise;
}

function loadChromePlugin () {
  return extension.loadPlugin().then(function (plugin) {
    return resolveObject(plugin);
  }).then(function (resolvedPlugin) {
    resolvedPlugin.wrapWithOldInterface = wrapNewPluginWithOldInterface;
    return resolvedPlugin;
  });
}

function onPluginLoaded (plugin, error) {
  wrapOldPluginWithNewInterface(plugin).then(function (wrappedPlugin) {
    if (loadCallbacks.length == 0) {
      throw "Internal error";
    }
  })

  var callback = loadCallbacks.shift();
  callback(wrappedPlugin);
}

function resolveObject (obj) {
  var resolvedObject = {};
  var promises = [];

  for (var m in obj) {
    (function (m) {
      if (isFunction(obj[m].then)) {
        promises.push(obj[m].then(function (result) {
          return resolveObject(result).then(function (resolvedProperty) {
            if (isFunction(resolvedProperty)) {
              resolvedObject[m] = proxyMember(obj, m);
            } else {
              resolvedObject[m] = resolvedProperty;
            }
          });
        }));
      } else {
        resolvedObject[m] = obj[m];
      }
    })(m);
  }
}

```

```

if (promises.length == 0) {
    return new Promise(function (resolve) {
        resolve(obj);
    });
} else {
    return Promise.all(promises).then(function () {
        return resolvedObject;
    });
}

function wrapNewPluginWithOldInterface () {
    var wrappedPlugin = {};

    for (var m in this) {
        if (isFunction(this[m])) {
            wrappedPlugin[m] = (function(plugin, member) {
                return function() {
                    var successCallback = arguments[arguments.length - 2];
                    var errorCallback = arguments[arguments.length - 1];
                    var args = Array.prototype.slice.call(arguments, 0, -2);
                    return member.apply(plugin, args).then(function (result) {
                        successCallback(result);
                    }, function (error) {
                        errorCallback(error.message);
                    });
                };
            })(this, this[m]);
        } else {
            wrappedPlugin[m] = this[m];
        }
    }

    return new Promise(function (resolve) {
        resolve(wrappedPlugin);
    });
}

function wrapOldPluginWithOldInterface () {
    var unwrappedPlugin = { originalObject: this.originalObject };

    for (var m in this.originalObject) {
        unwrappedPlugin[m] = proxyMember(this.originalObject, m);
    }

    return new Promise(function (resolve) {
        resolve(unwrappedPlugin);
    });
}

function wrapOldPluginWithNewInterface (plugin) {
    var wrappedPlugin = {
        originalObject: plugin,
        wrapWithOldInterface: wrapOldPluginWithOldInterface
    };

    for (var m in plugin) {
        if (isFunction(plugin[m])) {
            wrappedPlugin[m] = (function (plugin, member) {
                return function() {
                    var args = Array.prototype.slice.call(arguments);
                    return new Promise(function (resolve, reject) {
                        args.push(resolve, reject);
                        member.apply(plugin, args);
                    });
                };
            })(plugin, plugin[m]);
        } else {
            wrappedPlugin[m] = plugin[m];
        }
    }

    return new Promise(function (resolve) {
        resolve(wrappedPlugin);
    });
}

if (extension) {
    initializeExtension();
} else if (navigator.mimeTypes && navigator.mimeTypes[pluginMimeType]) {
    initialize();
} else {
    try {
        var plugin = new ActiveXObject("Aktiv.CryptoPlugin");
    }
}

```

```
    initialize();  
  } catch (e) {  
    initializeWithoutPlugin();  
  }  
}  
  
return my;  
}(rutoken || {}));  
  
if (typeof module !== 'undefined') {  
  module.exports = rutoken;  
}
```